



Galaxy™ 4826 Full Dimension Barrier Hose

[Contact us by Email.](#)

Features

- . Two Polyester spiral barrier hose
- . J51 A II Outside Diameters
- . Compatible with
 - . R-12 / R134a refrigerants
 - . Mineral oil / PAG's
- . Dimensionally Stable
- . Flexible -- Easy to Route



Specifications

Permeation: 1.77 Kg /m² / year

Moisture Ingression: 0.056 g / cm² / yr

Temperature Range: -40°F to 257° F (-40°C / 125°C)

Meets SAE J2064 TYPE C Class II

Construction: < CR PA NBR PET NBR PET EPDM >

Dash	Size		Inside Diameter				Outside Diameter				Weight	
			Inch		mm		Inch		mm			
	Inch	mm	min	max	min	max	min	max	min	max	lbs/ft	kg/m
-6	5/16	8	0.307	0.337	7.8	8.6	0.719	0.781	18.3	19.8	0.20	0.30
-8	13/32	10	0.401	0.436	10.2	11.1	0.875	0.937	22.2	23.8	0.28	0.42
-10	1/2	13	0.490	0.535	12.4	13.6	0.969	1.031	24.6	26.2	0.33	0.49
-12	5/8	16	0.615	0.660	15.6	16.8	1.094	1.156	27.8	29.4	0.38	0.57

The GOODYEAR (and Winged Foot Design) trademark is used by Veyance Technologies, Inc. under license from The Goodyear Tire & Rubber Company.

Goodyear Engineered Products are manufactured and sourced exclusively by Veyance Technologies, Inc. or its affiliates.

©2011 Veyance Technologies, Inc. All Rights Reserved.